PEEK® Secure-Fit Fittings

Single ended: cat.#s 25217-25220, 25230-25237

Double ended: cat.#s 25221—25229

Secure-Fit connectors are designed to ensure a leak-free seal and eliminate dead volume with any standard 1/16"-10/32 internal HPLC fitting connection port.

Instructions for Use:

- Push the Secure-Fit fitting into the port until the threads engage.
- Turn the Secure-Fit fitting until it is finger-tight.
 Secure-Fit fittings seal easily so only a light tightening is required to obtain a leak-free seal. The tubing penetration depth is automatically set.
- For double ended fittings, repeat the above steps.
- For single ended fittings, be sure to make a good zero dead volume connection at the other end of the tube with standard nuts and ferrules.

Call Technical Service at 800-356-1688 or 814-353-1300, ext. 4 (or your local Restek representative) if you have any questions about this product or any other Restek product.





Restek USA: 110 Benner Circle, Bellefonte, PA 16823 phone: (800) 356-1688 or (814) 353-1300 • fax: (814) 353-1309; www.restekcorp.com Restek GmbH: phone: (49) 06172 2797 0 • email: RESTEK-GMBH@t-online.de Restek France: phone: (33) 01 60 78 32 10 • email: restekfr@club-internet.fr Thames Restek UK Ltd.: phone: (44) 01753 624111 • email: Sales@Thamesrestek.co.uk Thames Restek Scotland Ltd.: phone: 0870 241 1247 • email: Sales@Thamesrestek.co.uk Restek Ireland: phone: (44) 2 890 814 576 • email: restekeurope@cs.com

